



# ORDERING INFORMATION

## ■ AVAILABILITY/PART NUMBER

Spray-On Version:

16 oz/470mL: 350-M-00014 PT

1 gal/3.8L: 350-M-00014 GL

5 gal/19L: 350-M-00014 PL

55 gal/209L: 350-M-00014 DR

Spray-On & Polish Kit:

16 oz/470mL: 350-M-00014 KIT

Polishing Sponge: 350-X-00004 (2/pk)

Immersion Version:

16 oz/470mL: 350-M-00015 PT

1 gal/3.8L: 350-M-00015 GL

5 gal/19L: 350-M-00015 PL

55 gal/209L: 350-M-00015 DR

## ■ COVERAGE

186 ft<sup>2</sup> (17 m<sup>2</sup>) of 1 mil (25µm) rust removal per gallon.

Axxaclean™ 2048 is ready to use without dilution.

## ■ SHELF LIFE & HANDLING

Shelf life of 2 years if stored out of direct sunlight. Zerust® Axxaclean™ 2048 may freeze below -10°F (-23°C), but will remain fully functional when thawed to ambient temperature. Store above 32°F (0°F).

## ■ DISPOSAL

Dispose of chemistry in compliance with applicable local, national and international regulations.

# ZERUST® AXXACLEAN™ 2048 PRODUCT INFORMATION

## ZERUST RUST REMOVER COMPARISON

Attributes	ICT®620-RR	Axxaclean 2048	Axxaclean 3048
<b>Corrosion Removal Power</b>	Light to medium rust even in cracks and crevices	Medium corrosion even in cracks and crevices	Heavy corrosion even in cracks and crevices
<b>Speed</b>	Slow	Moderate	Rapid
<b>Metals Treated</b>	Ferrous	Ferrous, brass, copper	Ferrous, brass, copper
<b>Application Methods</b>	Immersion	Immersion, Brush-On, Spray-On	Immersion, Brush-On
<b>pH Level</b>	Neutral pH of about 7	Mild acidic pH of about 2	Stronger acidic pH between 0.5-1.5
<b>Temperature For Use</b>	70°F (21°C) or above	70°F (21°C) or above	40°F (4°C) or above
<b>Compatibility (&lt;24 hour soak)</b>	Safe for metals*, paint, gaskets, rubber, plastics	Safe for metals*, paint, gaskets, rubber, plastics	May attack soft metals*, some paints and coatings
<b>Post-Cleaning Action</b>	Do not let product dry on surface. Water rinse, dry and wipe any carbon residue.	Do not let product dry on surface. Recommended DI or RO water rinse. Wipe off and dry well.	Do not let product dry on surface. Recommended DI or RO water rinse. Wipe off and dry well.
<b>Corrosion Protection</b>	Additional corrosion protection needed	Provides flash-corrosion protection in controlled environments	Provides flash-corrosion protection in controlled environments
<b>Environmental Disposal</b>	Non-hazardous. Pure product is neutral. Check local, national and international regulations.	Check for options for neutralizing. Check local, national and international regulations.	Do not dispose into waterways. Check local, national and international regulations.
<b>Personal Protection</b>	Optional gloves and eye protection	Gloves and eye protection	Ventilation, gloves, face shield and apron

\*Test before use on zinc and cadmium. Check with your Zerust technical representative for details.

## OTHER PRODUCTS AVAILABLE

### **Axxaclean™ 3048 Heavy Rust Remover**

Easy-to-use, fast acting and rust remover for extreme corrosion.

### **Axxanol™ Family of Corrosion Protective Coatings**

Use Z-Maxx for long-term outdoor corrosion protection.

### **ICT®500 Series: Packaging Films**

Our most widely used series of products. A variety of films offer short or long-term corrosion protection for parts and equipment during storage or shipment.

#### Warranty and Disclaimer Information:

We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied. See [www.zerust.com/warranty](http://www.zerust.com/warranty).

©2012 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: NTI®, ZERUST®, The ZERUST People®, ActivPak®, Cor-Tab®, Flange Saver®, Plastabs®, ICT®, COR-SCI®, Z-CIS® and the Color "Yellow". EXCOR®, VALENO®, ABRIGO® and UNICO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

**ZERUST®**  **EXCOR®**

A product of:  
**Northern Technologies International Corporation**  
 4201 Woodland Road  
 P.O. Box 69  
 Circle Pines, MN 55014  
 PH: +1 (763) 225-6600  
 FAX: +1 (763) 225-6645  
 EMAIL: [sales@zerust.com](mailto:sales@zerust.com)  
 WEB: [www.zerust.com](http://www.zerust.com)